

FA-370 ANTENNA



FEATURES

- ASSEMBLED IN LESS THAN 30 MINUTES
- NO TOOLS REQUIRED
- ONLY 5 CASES <470kgs
- MULTI-BAND FEEDS CHANGED IN MINUTES
- INTELSAT/EUTELSAT COMPLIANT FOR COMMERCIAL BANDS
- WGS, SKYNET, XTAR, INMARSAT AND MIL-STD-810G CERTIFIED
- COMPLETE, INTEGRATED SYSTEMS AVAILABLE

A 3.7m FLYAWAY ANTENNA FOR MULTI-BAND TRANSMISSIONS

The FA-370 is a compact ultra high gain antenna which can be easily deployed with no tools in less than 30 minutes.

All major components of the antenna including the multi-segmented reflector plus integrated 3 axis mount and flight case system are moulded from carbon fibre, which makes it more practical to transport than many much smaller antennas, yet the 3.7m diameter allows for an uplink EIRP previously unachievable from a flyaway earth station.

GigaSat's high precision manufacturing process ensures excellent surface accuracy on the dish and guarantees no deformation, even after being assembled hundreds of times.

The FA-370 is ideal for any rapid deployment broad band communications requirement such as MCPC digital video or multiple SCPC transmission. Secure Government Communications, Emergency Restoration, Sporting Events and Major news stories are obvious applications.

Each FA-370 antenna has a four piece segmented feed arm which allows operation at C, X, Ku, DBS and Ka band frequencies.

Band changes are achieved simply by clipping the relevant feed cartridge into position.

The axially symmetric prime focus feed system was chosen because of its overall compact dimensions and commonality of spare parts. A spares holding of only two petals is all that's required to repair a reflector in case of damage. Compliance with all satellite authority specifications is guaranteed, including side lobe performance better than 29-25 log θ .

Vernier adjustments with clear scales are included for all three axes including fine and course adjustment for elevation and in common with all FA series antennas the FA-370 has a full 0 to 90 degree elevation capability.

WGS, Skynet, Inmarsat and XTAR certified systems are available.

SPECIFICATIONS

General	
Antenna Type	Circular, axially symmetric with centre hub plus eighteen petals
Diameter	3.7m
Configuration	Prime Focus
Polarisation	Linear orthogonal transmit & receive. (Optional circular left & right)
Cross Polarisation	-35dB within the -1dB co-polar contour (linear)
Port-to-Port Isolation	40dB (Linear)

Transmit		
Transmit Bands	FA-370/60 FA-370/70 FA-370/140 FA-370/180 FA-370/300	5.85 to 7.025GHz 7.9 to 8.4GHz 12.75 to 14.5GHz 17.3 to 18.4GHz 27.5 to 31GHz
3dB Beamwidth	<1.0° at 5.85GHz	
Transmit Power	1.5kW max.	
Off Axis Transmit Gain	<29-25 logθ dBi	
VSWR	1.3:1	
Transmit Gain	FA-370/60 FA-370/70 FA-370/140 FA-370/180 FA-370/300	45.3dBi mid-band 47.7dBi mid-band 52.5dBi mid-band 54.6dBi mid-band 58.4dBi mid-band

Receive		
Receive Bands	FA-370/60 FA-370/70 FA-370/140 FA-370/180 FA-370/300	3.4 to 4.2GHz 7.25 to 7.75GHz 10.7 to 12.75GHz 10.7 to 12.75GHz 17.7 to 22.2GHz
Receive Gain	FA-370/60 FA-370/70 FA-370/140 FA-370/180 FA-370/300	40.9dBi mid-band 47.0dBi mid-band 50.5dBi mid-band 50.5dBi mid-band 54.8dBi mid-band

Power	
Power Requirement	90 to 264V AC Power Supply (option) +24V DC (option)

Environmental	
Temperature	-40 to +70°C - Transportation & Storage -20 to +60°C - Operational
Humidity	1 to 100%
Altitude	4,500m
Wind Rating	Operational 60km/h with gusts to 72km/h Survival 121km/h

Physical	
Elevation Adjustment	0 to 90°
Azimuth Adjustment	+/-180°
Polarisation Adjustment	+/-95°
Packed Size	Box 1 1.23 x 1.23 x 0.55m Box 2 1.23 x 1.23 x 0.55m Box 3 1.23 x 1.23 x 0.55m Box 4 1.23 x 1.23 x 0.5m Box 5 1.23 x 1.23 x 0.5m
Weight	Box 1 77kgs Box 2 77kgs Box 3 107kgs Box 4 118kgs Box 5 83kgs Weights above are for manual, baseline, configuration



Quad-band Feed arms—C/X, Ku & Ka (C/X, Ku/DBS & Ka available as an option)



making a difference

Ultra Electronics
GIGASAT
 Tring Business Centre
 Icknield Way
 Tring
 Hertfordshire, HP23 4JX
 United Kingdom
 Tel: +44 1442 892000
 Email: enquiries@ultra-gigasat.com
 www.ultra-gigasat.com
 www.ultra-electronics.com

Ultra Electronics reserves the right to vary these specifications without notice.
 © Ultra Electronics Limited 2016.
 Printed in England