

MicroVSAT TERMINAL



FEATURES

- ON AIR IN MINUTES
- NO TOOLS REQUIRED
- Ka AND X-BAND VERSIONS
- SIMPLICITY OF A BGAN TERMINAL
- HIGH DATA RATE COMMUNICATIONS
- MODEM AGNOSTIC, L-BAND INTERFACE
- COMPLETE INTEGRATED SYSTEM

LIGHT AND COMPACT FLAT PANEL ANTENNA (22lbs) WITH MANUAL SATELLITE ACQUISITION

The MicroVSAT terminal utilises a custom flat panel array.

This rugged suitcase MicroVSAT terminal offers the simplicity of a BGAN terminal with the increased through-put of Commercial and Military satellites.

The complete terminal is designed to be carried as airline cabin luggage.

The standard terminal is offered with an embedded iDirect Evolution modem.

The modem incorporates Adaptive Coding and Modulation (ACM), required for Ka-band operation.

The terminal is designed to be modem agnostic and can house a number of modem options including, but not limited to:

iDirect e150 (integral)
iDirect e850 (external)
iDirect 950 (integral)
Comtech DMD1050 (external)
Paradise Q-Lite (integral)
Hughes HX280 (external)

It is possible to bypass or omit an internal modem and connect an external modem using the L-band interfaces.

The terminal incorporates a simple pointing system using a highly intuitive Graphical User Interface to peak the antenna onto the chosen satellite.

The embedded control board controls all functions of the terminal and allows external control via Ethernet.

Data is connected to the terminal using a RJ45 Ethernet connector.

Different size BUCs can be externally connected to the terminal, should increased EIRP be required.

An additional flat panel can be clipped in place, in-field, as another means of increasing EIRP.

The terminal can be powered by DC (11 to 30VDC) or mains (90 to 264VAC) using an external AC-DC adapter.

SPECIFICATIONS

General	
Antenna Type	Flat panel
Dimensions of panel	MV-023 8" x 8" (0.2m x 0.2m) MV-032 8" x 16" (0.2m x 0.41m) Option
Polarisation	LHCP/RHCP
Axial Ratio	1.0dB (Tx) 1.5dB (Rx)

Transmit		
Transmit Bands	MV-070 (X) MV-300 (Ka) MV-300 (Ka)	7.9 to 8.4GHz 29.0 to 30.0GHz 30.0 to 31.0GHz
3dB Beamwidth	<3.1° at 30.5GHz	For 8" x 8" panel
VSWR	1.3:1	
Transmit Gain	MV-023/70 MV-032/70 MV-023/300 MV-032/300	23.1dBi mid-band 26.0dBi mid-band 35.2dBi mid-band 37.6dBi mid-band
Transmit EIRP Linear (PSat)	MV-023/70 MV-032/70 MV-023/300 MV-032/300	33.1dBW (36.1dBW) 36.0dBW (39.0dBW) 43.5dBW (45.0dBW) 46.0dBW (47.5dBW)
Higher EIRPs are possible using larger BUC and external power supply		

Terminal User Interface
Simple Intuitive User interface via Graphical Display
Audible Output for Satellite Acquisition
Web Browser Setup
Network Management System (Option)

Satellite Acquisition
Via Modem SNR or Rx Signal Level
Beacon Receiver (Option)

Receive		
Receive Bands	MV-070 (X) MV-300 (Ka) MV-300 (Ka)	7.25 to 7.75GHz 19.2 to 20.2GHz 20.2 to 21.2GHz
Receive Gain	MV-023/70 MV-032/70 MV-023/300 MV-032/300	22.8dBi mid-band 25.5dBi mid-band 34.2dBi mid-band 37.0dBi mid-band
Receive G/T	MV-023/70 MV-032/70 MV-023/300 MV-032/300	2.1dB/K 5.0dB/K 11.0dB/K 13.5dB/K

Power	
Power Requirement	+11 to 30V DC External battery (Option) External mains (90 to 264VAC) adaptor (Option)
Power Consumption	150W Maximum (PSat) 130W Typical Operation (PLin) <50W Receive Only

Environmental	
Temperature	-40 to +70°C - Transportation & Storage -20 to +55°C - Operational
Humidity	MIL-STD-810G 507.5, Proc II
Altitude	MIL-STD-810G 500.5, Proc II, 15,000ft
Wind Rating	45mph (72km/h) - Operational 65mph (104km/h) - Survival
Shock	MIL-STD-810G 516.6 Proc. I
Shock—Transit Drop	MIL-STD-810G 516.6 Proc. IV
Vibration	MIL-STD-810G 514.6 Proc. I, Cat 24
Ingress Protection	IP65

Physical	
Elevation Adjustment	0 to 90°
Azimuth Adjustment	360°
Packed Size	10.7" x 11.5" x 8.5" (272 x 292 x 216mm)
Weight	22lbs (10kgs)



making a difference

Ultra Electronics
GIGASAT
 Tring Business Centre
 Icknield Way
 Tring
 Hertfordshire, HP23 4JX
 United Kingdom
 Tel: +44 1442 892000
 Email: enquiries@ultra-gigasat.com
 www.ultra-gigasat.com
 www.ultra-electronics.com

Ultra Electronics
GIGASAT
 2158 Renard Court
 Annapolis
 Maryland 21401
 USA
 Tel: +1 443 994 2100
 Email: enquiries@ultra-gigasat.com
 www.ultra-gigasat.com
 www.ultra-electronics.com

Ultra Electronics reserves the right to vary these specifications without notice.
 © Ultra Electronics Limited 2016.
 Printed in England